

Uncontrolled document as of October 14, 2007. Refer to website for up to date specifications.

CASES 1150 Case



1150 Case

- **Watertight, crushproof, and dust proof**
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Unconditional Lifetime Guarantee of Excellence

1150 Case Configurations

Cat. #	Description
1150	1150 Case
1150NF	1150 Case (No foam)



Black



Silver



Orange



Yellow



Blue



OD Green*



Desert Tan

*OD Green available upon request

1150 Case Specifications

Exterior Dimensions (L x W x D)

9.12" x 7.56" x 4.37" (23.2 x 19.2 x 11.1 cm)

Lid Depth

0.75" (1.9 cm)

Weight with Foam

1.98 lbs. (0.9 kg)

Range Temperature

-10 / 210° F
(-23 / 99° C)

Interior Dimensions (L x W x D)

8.18" x 5.68" x 3.62" (20.8 x 14.4 x 9.2 cm)

Bottom Depth

2.87" (7.3 cm)

Weight without Foam

1.76 lbs. (0.8 kg)

Total Depth

3.62" (9.2 cm)

Buoyancy Max.

8 lbs.
(3.63 kg)

1150 Case Certificates

• IP67 • Def Stan 81-41/STANAG 4280

1150 Case Accessories

Cat. #	Description	Sug. Retail
1150PF	Special Application Panel Frame	\$11.95
1151	3 pc. Replacement Foam Set	\$12.50
1153	Replacement O-ring	\$3.15

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com