

Uncontrolled document as of October 14, 2007. Refer to website for up to date specifications.

**CASES**  
**1200**  
**Case**



**1200 Case**

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Unconditional Lifetime Guarantee of Excellence

**1200 Case Configurations**

Cat. #	Description
1200	1200 Case
1200NF	1200 Case (No foam)



Black



Silver



Orange



Yellow



OD Green\*



Desert Tan

\*OD Green available upon request

**1200 Case Specifications**

**Exterior Dimensions (L x W x D)**

10.62" x 9.68" x 4.87" (27 x 24.6 x 12.4 cm)

**Lid Depth**

1.18" (3 cm)

**Weight with Foam**

2.87 lbs. (1.3 kg)

**Range Temperature**

-10 / 210° F  
(-23 / 99° C)

**Interior Dimensions (L x W x D)**

9.25" x 7.12" x 4.12" (23.5 x 18.1 x 10.5 cm)

**Bottom Depth**

2.93" (7.4 cm)

**Weight without Foam**

2.65 lbs. (1.2 kg)

**Total Depth**

4.11" (10.4 cm)

**Buoyancy Max.**

12.02 lbs.  
(5.45 kg)

**1200 Case Certificates**

- IP67 • Def Stan 81-41/STANAG 4280

**1200 Case Accessories**

Cat. #	Description	Sug. Retail
1200PF	Special Application Panel Frame	\$11.95
1201	3 pc. Replacement Foam Set	\$17.50
1203	Replacement O-ring	\$3.55

**Pelican™ Products, Inc.**

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
e-mail: [sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)