

Uncontrolled document as of October 14, 2007. Refer to website for up to date specifications.

**CASES**  
**1300**  
**Case**



**1300 Case**

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Unconditional Lifetime Guarantee of Excellence

**1300 Case Configurations**

Cat. #	Description
1300	1300 Case
1300NF	1300 Case (No foam)



\*OD Green available upon request

**1300 Case Specifications**

**Exterior Dimensions (L x W x D)**

10.62" x 9.68" x 6.87" (27 x 24.6 x 17.4 cm)

**Lid Depth**

1.18" (3 cm)

**Weight with Foam**

3.53 lbs. (1.6 kg)

**Range Temperature**

-10 / 210° F  
(-23 / 99° C)

**Interior Dimensions (L x W x D)**

9.87" x 7.00" x 6.12" (25.1 x 17.8 x 15.5 cm)

**Bottom Depth**

4.93" (12.5 cm)

**Weight without Foam**

3.09 lbs. (1.4 kg)

**Total Depth**

6.11" (15.5 cm)

**Buoyancy Max.**

12.35 lbs.  
(5.6 kg)

**1300 Case Certificates**

• IP67 • Def Stan 81-41/STANAG 4280

**1300 Case Accessories**

Cat. #	Description	Sug. Retail
1200PF	Special Application Panel Frame	\$11.95
1203	Replacement O-ring	\$3.55
1301	4 pc. Replacement Foam Set	\$21.50
1400IP	Instapak Quick® RT	\$23.70

**Pelican™ Products, Inc.**

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
e-mail: [sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)