

Uncontrolled document as of October 14, 2007. Refer to website for up to date specifications.

CASES
1400
Case



1400 Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel padlock protectors
- Comfortable rubber over-molded handle
- Stainless steel hardware
- Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Unconditional Lifetime Guarantee of Excellence

1400 Case Configurations

Cat. #	Description
1400	1400 Case
1400NF	1400 Case (No foam)



Black



Silver



Orange



Yellow

*OD Green available upon request



OD Green*



Desert Tan

1400 Case Specifications

Exterior Dimensions (L x W x D)

13.37" x 11.62" x 6.00" (33.9 x 29.5 x 15.2 cm)

Lid Depth

1.18" (3 cm)

Weight with Foam

4.41 lbs. (2 kg)

Range Temperature

-10 / 210° F
(-23 / 99° C)

Interior Dimensions (L x W x D)

11.81" x 8.87" x 5.18" (30 x 22.5 x 13.2 cm)

Bottom Depth

4.00" (10.2 cm)

Weight without Foam

3.97 lbs. (1.8 kg)

Total Depth

5.18" (13.2 cm)

Buoyancy Max.

20.06 lbs.
(9.1 kg)

Personalized Nameplate Available

1400 Case Certificates

• IP67 • MIL C-4150J • Def Stan 81-41/STANAG 4280 • ATA 300

1400 Case Accessories

Cat. #	Description	Sug. Retail
1400IP	Instapak Quick® RT	\$23.70
1400PF	Special Application Panel Frame	\$12.95
1401	3 pc. Replacement Foam Set	\$29.50
1403	Replacement O-ring	\$4.25

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com