

Uncontrolled document as of October 14, 2007. Refer to website for up to date specifications.

CASES
1550
Case



1550 Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- 2 level Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Unconditional Lifetime Guarantee of Excellence

1550 Case Configurations

Cat. #	Description
1550	1550 Case
1550NF	1550 Case (No foam)
1554	1550 Case with Padded Dividers



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request

1550 Case Specifications

Exterior Dimensions (L x W x D)

20.62" x 16.87" x 8.12" (52.4 x 42.8 x 20.6 cm)

Lid Depth

1.75" (4.4 cm)

Weight with Foam

11.9 lbs. (5.4 kg)

Range Temperature

-10 / 210° F
(-23 / 99° C)

Interior Dimensions (L x W x D)

18.43" x 14.00" x 7.62" (46.8 x 35.5 x 19.3 cm)

Bottom Depth

5.87" (14.9 cm)

Weight without Foam

10.58 lbs. (4.8 kg)

Total Depth

7.62" (19.3 cm)

Buoyancy Max.

69.89 lbs.
(31.7 kg)

Personalized Nameplate Available

1550 Case Certificates

• IP67 • MIL C-4150J • Def Stan 81-41/STANAG 4280 • ATA 300

1550 Case Accessories

Cat. #	Description	Sug. Retail
1550IP	Instapak Quick® RT	\$39.70
1550PF	Special Application Panel Frame	\$14.95
1551	4 pc. Replacement Foam Set	\$66.95
1552	Pick 'N' Pluck™ Sections Only (set of 2)	\$51.95
1553	Replacement O-ring	\$4.85
1555	Padded Divider Set Only	\$139.95

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com