

Uncontrolled document as of October 14, 2007. Refer to website for up to date specifications.

CASES
1560
Case



1560 Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded top and side handles
- Stainless steel hardware and padlock protectors
- 2 level Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Unconditional Lifetime Guarantee of Excellence
- **Retractable extension handle**
- **Strong polyurethane wheels with stainless steel bearings**

1560 Case Configurations

Cat. #	Description
1560	1560 Case
1560NF	1560 Case (No foam)
1564	1560 Case with Padded Dividers



*OD Green available upon request

1560 Case Specifications

Exterior Dimensions (L x W x D)

22.06" x 17.93" x 10.43" (56 x 45.5 x 26.5 cm)

Lid Depth

2.00" (5.1 cm)

Weight with Foam

20 lbs. (9.07 kg)

Range Temperature

-10 / 210° F
(-23 / 99° C)

Interior Dimensions (L x W x D)

20.37" x 15.43" x 9.00" (51.7 x 39.2 x 22.9 cm)

Bottom Depth

7.00" (17.8 cm)

Weight without Foam

17 lbs. (7.71 kg)

No. of Wheels

2

Total Depth

9.00" (22.9 cm)

Buoyancy Max.

104 lbs.
(47.17 kg)

Personalized Nameplate Available

1560 Case Certificates

- IP67 • Def Stan 81-41/STANAG 4280

1560 Case Accessories

Cat. #	Description	Sug. Retail
0343	Replacement O-ring	\$5.10
1550IP	Instapak Quick® RT	\$39.70
1561	4 pc. Replacement Foam Set	\$68.95
1562	Pick 'N' Pluck™ Sections Only (set of 2)	\$51.95
1565	Padded Divider Set Only	\$154.95
1569	Lid Organizer for 1560 Case	\$42.95

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com