

Uncontrolled document as of October 14, 2007. Refer to website for up to date specifications.

CASES
1610
Case



1610 Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel hardware and padlock protectors
- 3 level Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Unconditional Lifetime Guarantee of Excellence
- **Retractable extension handle**
- **Strong polyurethane wheels with stainless steel bearings**

1610 Case Configurations

Cat. #	Description
1610	1610 Case
1610NF	1610 Case (No foam)
1614	1610 Case with Padded Dividers



Black



OD Green*



Desert Tan

*OD Green available upon request

1610 Case Specifications

Exterior Dimensions (L x W x D)

24.71" x 19.58" x 11.93" (62.7 x 49.7 x 30.3 cm)

Lid Depth

2.06" (5.2 cm)

Weight with Foam

22.49 lbs. (10.2 kg)

Range Temperature

-10 / 210° F
(-23 / 99° C)

Interior Dimensions (L x W x D)

21.68" x 16.62" x 10.56" (55 x 42.2 x 26.8 cm)

Bottom Depth

8.50" (21.6 cm)

Weight without Foam

20 lbs. (9.07 kg)

No. of Wheels

2

Total Depth

10.56" (26.8 cm)

Buoyancy Max.

119.93 lbs.
(54.4 kg)

Personalized Nameplate Available

1610 Case Certificates

- IP67 • Def Stan 81-41/STANAG 4280

1610 Case Accessories

Cat. #	Description	Sug. Retail
1600IP	Instapak Quick® RT	\$45.70
1609	Lid Organizer	\$43.95
1611	5 pc. Replacement Foam Set	\$95.95
1612	Pick 'N' Pluck™ Sections Only (set of 3)	\$76.95
1613	Replacement O-ring	\$5.15
1615	Padded Divider Set Only	\$157.95

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com