

Uncontrolled document as of October 14, 2007. Refer to website for up to date specifications.

CASES
1620
Case



1620 Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel hardware and padlock protectors
- 4 level Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Unconditional Lifetime Guarantee of Excellence
- **Retractable extension handle**
- **Strong polyurethane wheels with stainless steel bearings**

1620 Case Configurations

Cat. #	Description
1620	1620 Case
1620NF	1620 Case (No foam)
1624	1620 Case with Padded Dividers



Black



OD Green*



Desert Tan

*OD Green available upon request

1620 Case Specifications

Exterior Dimensions (L x W x D)

24.81" x 19.37" x 13.87" (63 x 49.2 x 35.2 cm)

Lid Depth

2.06" (5.2 cm)

Weight with Foam

26.01 lbs. (11.8 kg)

Range Temperature

-10 / 210° F
(-23 / 99° C)

Interior Dimensions (L x W x D)

21.37" x 16.31" x 12.56" (54.3 x 41.4 x 31.9 cm)

Bottom Depth

10.50" (26.7 cm)

Weight without Foam

24.47 lbs. (11.1 kg)

No. of Wheels

2

Total Depth

12.56" (31.9 cm)

Buoyancy Max.

149.91 lbs.
(68 kg)

Personalized Nameplate Available

1620 Case Certificates

• IP67 • MIL C-4150J • Def Stan 81-41/STANAG 4280

1620 Case Accessories

Cat. #	Description	Sug. Retail
1600IP	Instapak Quick® RT	\$45.70
1609	Lid Organizer	\$43.95
1621	6 pc. Replacement Foam Set	\$97.95
1622	Pick 'N' Pluck™ Sections Only (set of 4)	\$76.95
1623	Replacement O-ring	\$5.60
1625	Padded Divider Set Only	\$254.95

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com