

Uncontrolled document as of October 14, 2007. Refer to website for up to date specifications.



1780T Transport Case



- The new class of **XXL Pelican Transport Cases**
- 50/50 lid-to-base ratio for easy loading
- Completely detachable lid for full access
- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel padlock protectors
- Pick 'N' Pluck™ foam configuration available
- 4 strong polyurethane wheels with stainless steel bearings
- Personalized nameplate service available
- Unconditional Lifetime Guarantee of Excellence

1780T Transport Case Configurations

Cat. #	Description
1780T	1780T Transport Case
1780TNF	1780T Transport Case (No foam)



*OD Green available upon request

1780T Transport Case Specifications

Exterior Dimensions (L x W x D)

44.90" x 25.32" x 16.50" (114 x 64.3 x 41.9 cm)

Lid Depth

7.58" (19.2 cm)

Weight with Foam

49 lbs. (22.23 kg)

Range Temperature

-10 / 210° F
(-23 / 99° C)

Interior Dimensions (L x W x D)

42.00" x 22.00" x 15.10" (106.6 x 55.9 x 38.3 cm)

Bottom Depth

7.30" (18.5 cm)

Total Depth

14.88" (37.8 cm)

Weight without Foam

38.4 lbs. (17.42 kg)

Buoyancy Max.

500 lbs.
(226.8 kg)

No. of Wheels

4

Personalized Nameplate Available

1780T Transport Case Certificates

- Def Stan 81-41/STANAG 4280

1780T Transport Case Accessories

Cat. #	Description	Sug. Retail
1781	6 pc. Replacement Foam Set	\$239.95
1782	Pick 'N' Pluck™ Sections Only (set of 4)	\$199.95
1783	Replacement O-ring	\$8.95

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com